


# RICOH

# Aficio™

MP 6001  
MP 7001  
MP 8001  
MP 9001



high  
volume



reap  
unexpected  
benefits



digital  
power



### PRINTER (OPTION)

|                              |   |
|------------------------------|---|
| Print speed:                 | 60/70/80/90 prints per minute   |
| Printer language/resolution: | Standard: RPCS, PCL5e, PCL6, Option: Adobe® PostScript™ 3, IPDS   |
| Interface:                   | Standard: Ethernet 10 base-T/100 base-TX, USB 2.0, Option: Parallel port IEEE1284, Wireless LAN (IEEE802.11 a/b/g), Bluetooth, 1000 base-T Ethernet   |
| Memory:                      | 1.5 GB + 160 GB Hard Disk Drive   |
| Network protocol:            | IPv4, IPv6, IPX/SPX, SMB, Apple Talk  |
| Supported environments:      | Windows® 2000/XP/Vista/ Server 2003/ Server 2008, Macintosh OS 8.6 or later (OS X classic), Macintosh OS X 10.1 or later (native mode), Novell® Netware® 3.12/3.2/4.1/4.11/5.0/5.1/6/6.5, UNIX Sun® Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11iv2/11iv3, SCO OpenServer 5.0.6/5.0.7/6.0, RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise, IBM AIX v4.3 & 5L v5.1/5.2/5.3, SAP R/3 3.x or later, mySAP ERP2004 or later |

|                         |  |
|-------------------------|--|
| ADF capacity:           | 150 - 250 sheets (less than 80 - 69 g/m <sup>2</sup> )   |
| Paper output capacity:  | Standard: 500 (A4), 250 (A3) sheets  |
| Paper size:             | A6 - A3  |
| Paper weight:           | Paper trays: 52.3 - 127.9 g/m <sup>2</sup><br>Bypass tray: 52.3 - 216 g/m <sup>2</sup><br>Duplex tray: 64 - 127.9 g/m <sup>2</sup> |
| Dimensions (W x D x H): | 690 x 790 x 1,165 mm   |
| Weight:                 | Less than 217 kg   |
| Power source:           | 220 - 240 V, 50 - 60 Hz  |
| Power consumption:      | Max.: 1.9/1.9/1.95/1.9 kW  |

### SOFTWARE SOLUTIONS

|           |  |
|-----------|--|
| Standard: | SmartDeviceMonitor™ for Admin, Web SmartDeviceMonitor™, Web Image Monitor, DeskTopBinder™ Lite, TWAIN driver, Printer utility for Macintosh, Agfa Font Manager |
| Option:   | DeskTopEditor™ For Production, SCS/IPDS printing   |

### SCANNER (OPTION)

|                               |   |
|-------------------------------|---|
| Scan speed:                   | FC - B/W: Max. 55 - 80 (simplex), Max. 90 - 130 originals per minute (duplex) |
| Resolution:                   | Max. 600 dpi (TWAIN: 1,200 dpi)   |
| Original size:                | Max. 297 mm x 432 mm  |
| Output formats:               | PDF, JPEG, TIFF   |
| Bundled drivers:              | Network TWAIN, WIA, WSD   |
| Scan to e-mail:               | SMTP, TCP/IP  |
| Destination addresses:        | Max. 500 per job  |
| Stored destination addresses: | Max. 2,000  |
| Address book:                 | Via LDAP or locally on Hard Disk Drive  |
| Scan to folder:               | Via SMB, FTP or NCP protocol  |
| Destination:                  | Max. 50 folders per job   |

### FAX (OPTION)

|                     |  |
|---------------------|--|
| Circuit:            | PSTN, PBX  |
| Compatibility:      | ITU-T (CCITT) G3, ITU-T (T.37) Internet fax, ITU-T (T.38) IP fax |
| Modem speed:        | Max.: 33.6 Kbps  |
| Resolution:         | Standard/detail: 200 x 100 - 200 dpi<br>Option: 400 x 400 dpi    |
| Compression method: | MH, MR, MMR, JBIG  |
| Scanning speed:     | Less than 0.70 seconds   |
| Memory capacity:    | Standard: 4 MB, Option: 32 MB                                    |
| Memory backup:      | Yes (one hour)   |

### OTHER OPTIONS

4,000-sheet A4 LCT, LG tray for A4 LCT, 1,000-sheet A3 tray, Tab sheet unit, Copy tray, Multi-folding unit, Cover interposer, 3,000-sheet finisher with 50-sheet stapler, 3,000-sheet finisher with 100-sheet stapler, 2,000-sheet saddle-stitch unit with 50-sheet stapler, 9-bin mailbox, Several punch units, Jogger unit for finisher, GBC StreamPunch™ III, Plockmatic booklet maker, @Remote, GlobalScan NX, G3 interface unit, Data Overwrite Security Unit, HDD Encryption Unit, Copy Data Security Unit, File Format Converter, VM Card, Browser Unit, Key counter and card bracket, Front SD/USB slot, Copy connector

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency. For availability of models, options and software, please consult your local Ricoh supplier.

### COPIER

|                       |   |
|-----------------------|---|
| Copying process:      | Four laser beams & electro-photographic printing  |
| Copy speed:           | 60/70/80/90 copies per minute (A4)  |
| Resolution:           | 1,200 dpi   |
| Multiple copy:        | Up to 999   |
| Warm-up time:         | Less than 30/30/60/300 seconds  |
| First copy speed:     | Less than 4.2/3.5/3.5/3.3 seconds   |
| Zoom:                 | 25 - 400% (in 1% steps)   |
| Memory:               | Max.: 1.5 GB + 160 GB Hard Disk Drive   |
| Paper input capacity: | Standard: 2 x 1,550-sheet paper tray(s), 2 x 550-sheet paper tray(s), 100-sheet bypass tray, Max.: 8,300 sheets |



Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

# RICOH

URL: <http://www.ricoh.co.in>

#### RICOH INDIA LIMITED

CORPORATE OFFICE: 52-B, Okhla Industrial Estate Phase-III, New Delhi - 110 020

Tel: (011) 41613010-18 Fax: (011) 41612221/ 3019 Email: [ril.info@ricoh.co.in](mailto:ril.info@ricoh.co.in)

REGISTERED OFFICE: 1104, Arcadia, NCPA Road, Nariman Point, Mumbai - 400 021

Tel: (022) 22881953/ 54/ 55 Fax: (022) 22881950

Ahmedabad, Bangalore, Bhopal, Bhubaneswar, Chandigarh, Chennai, Coimbatore, Delhi, Guwahati, Hyderabad, Jaipur, Kochi, Kolkata, Lucknow, Mumbai, Nagpur, Patna, Pune, Ranchi, Visakhapatnam.

**For more information, please contact:**